







SWAGED WIRE ROPE SLINGS

The Flemish eye, mechanically spliced with a carbon steel sleeve, offers the greatest safety in a wire rope choker. Proof testing and sling certification available upon request.



6 X 19 Class - Extra Improved Plow Steel IWRC						
		Rated Capacity In Tons				
Cable Diameter	Minimum Length	 Choker	 Vertical	 90° Basket	Eye Width (Inches)	Eye Length (Inches)
1/4"	1' - 6"	.48	.65	1.3	2"	4"
5/16"	1' - 9"	.75	1.0	2.0	2-1/2"	5"
3/8"	2' - 0"	1.1	1.4	2.9	3"	6"
1/2"	2' - 6"	1.9	2.5	5.1	4"	8"
5/8"	3' - 0"	2.9	3.9	7.8	5"	10"
3/4"	3' - 6"	4.1	5.6	11.0	6"	12"
7/8"	4' - 0"	5.6	7.6	15.0	7"	14"
1"	4' - 6"	7.2	9.8	20.0	8"	16"



6 X 37 Class - Extra Improved Plow Steel IWRC						
		Rated Capacity In Tons				
Cable Diameter	Minimum Length	 Choker	 Vertical	 90° Basket	Eye Width (Inches)	Eye Length (Inches)
1 - 1/8"	5' - 0"	9.1	12.0	24.0	9"	18"
1 - 1/4"	5' - 6"	11.0	15.0	30.0	10"	20"
1 - 3/8"	6' - 0"	13.0	18.0	36.0	11"	22"
1 - 1/2"	7' - 0"	16.0	21.0	42.0	12"	24"