




## WEIGHT CAPACITY AND SIZE OF HARDWARE FOR CABLE BRIDLES

### TWO LEG BRIDLES

#### RATED CAPACITY (TONS)



CABLE DIA.	MINIMUM LEG LENGTH	RATED CAPACITY (TONS)			O-RING SIZE	*EYE HOOK SIZE
		30° 	45° 	60° 		
1/4"	1'-3"	0.65	0.91	1.1	1/2"	1 TON A
3/8"	1'-8"	1.4	2.0	2.5	3/4"	2 TON A
1/2"	2'-0"	2.5	3.6	4.4	3/4"	3 TON A
5/8"	2'-4"	3.9	5.5	6.8	1"	4.5 TON A
3/4"	2'-9"	5.6	7.9	9.7	1-1/4"	5 TON C
7/8"	3'-3"	7.6	11.0	13.0	1-1/4"	7.5 TON C
1"	3'-6"	9.8	14.0	17.0	1-1/2"	10 TON C

### THREE LEG BRIDLES



1/4"	1'-3"	0.97	1.4	1.7	1/2"	1 TON A
3/8"	1'-8"	2.2	3.0	3.7	3/4"	2 TON A
1/2"	2'-0"	3.8	5.4	6.6	1"	3 TON A
5/8"	2'-4"	5.9	8.3	10.0	1-1/4"	4.5 TON A
3/4"	2'-9"	8.4	12.0	15.0	1-1/2"	5 TON C
7/8"	3'-3"	11.0	16.0	20.0	1-1/2"	7.5 TON C
1"	3'-6"	15.0	21.0	26.0	1-3/4"	10 TON C

### FOUR LEG BRIDLES



3/8"	1'-8"	2.9	4.1	5.0	1"	2 TON A
1/2"	2'-0"	5.1	7.1	8.8	1-1/4"	3 TON A
5/8"	2'-4"	7.8	11.0	14.0	1-1/4"	4.5 TON A
3/4"	2'-9"	11.0	16.0	19.0	1-3/4"	5 TON C
7/8"	3'-3"	15.0	21.0	26.0	1-3/4"	7.5 TON C
1"	3'-6"	20.0	28.0	34.0	2-1/4"	10 TON C

\*EYE HOOK SIZE - A= ALLOY & C= CARBON