

TOW STRAPS

TOW (SAFER) STRAPS - MADE WITH LOOP ON EACH END.

**NEVER USE WITH CHAINS OR HOMEMADE HARDWARE.
SELECT THE RIGHT SIZE OF TOW STRAP FOR YOUR TOWING NEEDS, USING THE
MANUFACTURER'S SAFE WORK LOAD LIMIT SPECIFICATIONS.**



PULL STRAP UNTIL TAUT, ALLOWING STRAP TO STRETCH.

FLAT TOW STRAP WEIGHT CAPACITIES							
SIZE	PLY	Working Load Limit (WLL) (In LBS.)	Breaking Strength (In LBS.)	SIZE	PLY	Working Load Limit (WLL) (In LBS.)	Breaking Strength (In LBS.)
1"	1 PLY	2,900	8,800	2"	1 PLY	5,800	17,600
1"	2 PLY	5,800	17,600	2"	2 PLY	11,700	35,200
1"	3 PLY	8,700	26,400	2"	3 PLY	17,600	52,800
1"	4 PLY	11,600	35,200	2"	4 PLY	23,200	70,400
3"	1 PLY	8,800	26,400	4"	1 PLY	11,700	35,200
3"	2 PLY	17,600	52,800	4"	2 PLY	23,400	70,400
3"	3 PLY	26,400	79,200	4"	3 PLY	35,100	105,600
3"	4 PLY	35,200	105,600	4"	4 PLY	46,800	140,800

*******CAUTION*******

- 1) NEVER EXCEED LOAD LIMIT.**
- 2) WATCH FOR SHARP OBJECTS THAT MAY DAMAGE YOUR STRAP.**
- 3) BE SAFE, REFRAIN FROM USING WRONG HARDWARE WITH STRAPS.**

(HEAVIER DUTY TOW STRAPS ARE LISTED ON THE NEXT PAGE.)

TOW STRAPS (Continued):



PULL STRAP UNTIL TAUT, ALLOWING STRAP TO STRETCH.

FLAT TOW STRAP WEIGHT CAPACITIES							
SIZE	PLY	Working Load Limit (WLL) (In LBS.)	Breaking Strength (In LBS.)	SIZE	PLY	Working Load Limit (WLL) (In LBS.)	Breaking Strength (In LBS.)
6"	1 PLY	17,500	53,000	8"	1 PLY	23,300	70,000
6"	2 PLY	35,000	106,000	8"	2 PLY	46,600	140,000
6"	3 PLY	52,500	159,000	8"	3 PLY	69,900	210,000
6"	4 PLY	70,000	212,000	8"	4 PLY	93,200	280,000
10"	1 PLY	29,300	88,000	12"	1 PLY	35,300	106,000
10"	2 PLY	58,600	176,000	12"	2 PLY	70,600	212,000
10"	3 PLY	87,900	264,000	12"	3 PLY	105,900	318,000
10"	4 PLY	117,200	352,000	12"	4 PLY	141,200	424,000