

VEHICLE RECOVERY - ROUND TOWING SLINGS



ROUND TOWING SLINGS			
SIZE	COLOR CODE	Working Load Limit (WLL) (In LBS.)	Breaking Strength (In LBS.)
NT 1	PURPLE	4,400	13,250
NT 2	GREEN	8,800	26,500
NT 3	YELLOW	11,200	33,600
NT 4	TAN	17,600	53,000
NT 5	RED	22,000	66,000
NT 6	ORANGE	28,000	84,000
NT 7	BLUE	35,000	106,000
NT 8	ORANGE	41,000	125,000
NT 9	ORANGE	52,800	158,500
NT 10	ORANGE	66,600	200,000
NT 11	ORANGE	88,100	264,500
NT 12	ORANGE	110,100	330,500
NT 13	ORANGE	150,000	450,000

SAFE OPERATING PRACTICES:

*Do not use a defective or damaged strap - inspect before each use. Watch for signs of: Holes, snags, tears, cuts, abrasion of core yarns; melting, charring, or chemical damage;

Worn or broken core yarns; Any other visible damage.

*Do not exceed the working load limit (WLL). *Do not tie knots in strap.

*Do not attach to bumpers. *Avoid dragging strap on the ground.

*Avoid heat damage from mufflers, exhaust systems.

*Stand clear of strap and object being towed when under load.

*Avoid abrasion from sharp edges - use webbing protectors.

*Store strap in cool, dry, dark location to prolong lifespan.