






## TYPE 2 - TRIANGLE - TRIANGLE NYLON SLING CAPACITIES



**(WORK LOAD LIMITS)**

Stock No.	Width (inches)	Ply	Vertical 	Basket Hitch Limits			
				90° 	60° 	45° 	30° 
TT1-902	2	1	3200	6400	5500	4500	3200
TT2-902	2	2	6400	12800	11100	9000	6400
TT4-902	2	4	11400	22800	19740	16120	11400
TT1-903	3	1	4800	9600	8300	6800	4800
TT2-903	3	2	8900	17800	15400	12600	8900
TT4-903	3	4	17000	34000	29440	24040	17000
TT1-904	4	1	6400	12800	11100	9000	6400
TT2-904	4	2	11200	22400	19400	15800	11200
TT4-904	4	4	22800	45600	39480	32240	22800
TT1-906	6	1	9600	19200	16600	13600	9600
TT2-906	6	2	16300	32600	28300	23100	16300
TT4-906	6	4	34000	68000	58890	48080	34000
TT1-908	8	1	12800	25600	22200	18100	12800
TT2-908	8	2	20500	41000	35500	29000	20500
TT4-908	8	4	40000	80000	69280	56560	40000
TT1-910	10	1	16000	32000	27700	22600	16000
TT2-910	10	2	24000	48000	41600	33900	24000
TT1-912	12	1	19200	38400	33200	27100	19200
TT2-912	12	2	26900	53700	46500	38000	26900

**RATED WEIGHT CAPACITIES IN POUNDS**