






**TYPE 6 - REVERSED EYE (STANDARD) NYLON SLING CAPACITIES AND
TYPE 7 - REVERSED EYE (FLAT) NYLON SLING CAPACITIES**



(WORK LOAD LIMITS)

Stock No.	Ply	Width (inches)	Eye Dimensions (Inches)		Vertical 	Choker 	Basket Hitch Limits		
			Width	Length			90° 	60° 	45° 
RE1-902	1	2	1"	9"	4500	3600	9000	7790	6360
RE2-902	2	2	1"	12"	7500	6000	15000	12990	10600
RE1-904	1	4	2"	12"	6400	5000	12800	11080	9050
RE2-904	2	4	2"	12"	11400	9000	22800	19740	16120
RE4-904	4	4	2"	18"	21500	17000	43000	37240	30400
RE1-906	1	6	1-1/2"	12"	9600	7600	19200	16630	13570
RE2-906	2	6	1-1/2"	18"	17000	13000	34000	29440	24040
RE4-906	4	6	3"	24"	34000	27000	68000	58890	48080

RATED WEIGHT CAPACITIES IN POUNDS

Reversed eye slings are completely covered in protective cordura wear pads. Reversed eye slings result in snug choke hitches while in use. The eye design also permits easier removal of the sling from under your load, once the load has been set. When ordering a Reversed Eye sling, state whether you want the Type 6 (standard eye) or the Type 7 (flat eye) sling.