





TYPE 8 - WIDE BODY BASKET NYLON SLING CAPACITIES



(WORK LOAD LIMITS)

Stock No.	Width (inches)	Ply	Basket Hitch Limits			
			90° 	60° 	45° 	30° 
WBB1-906	6	1	19200	18600	16600	13600
WBB2-906	6	2	35520	34300	30800	25100
WBB1-908	8	1	25600	24700	22200	18080
WBB2-908	8	2	46080	44500	39900	32500
WBB1-912	12	1	38400	37100	33300	27100
WBB2-912	12	2	65300	63100	56600	46100
WBB1-916	16	1	51200	49500	44400	36200
WBB2-916	16	2	81900	79200	71000	57800
WBB1-920	20	1	64000	61900	55500	45200
WBB2-920	20	2	96000	92800	83200	67800
WBB1-924	24	1	76800	74200	66600	54200
WBB2-924	24	2	107500	103900	93200	75900
RATED WEIGHT CAPACITIES IN POUNDS						

Wide body basket slings are made to offer better balance for support of your heavy loads. Stiffeners are used at the base of the eyes to deter the body of the sling from folding down the middle. Wide body basket slings are for use in a basket hitch only.

Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30 degrees.